



State of Ohio Environmental Protection Agency

Southeast District Office

2195 Front Street
Logan, Ohio 43138

TELE: (740) 385-8501 FAX: (740) 385-6490
www.epa.state.oh.us

Ted Strickland, Governor
Lee Fisher, Lieutenant Governor
Chris Korleski, Director

June 24, 2008

**Re: Muskingum County
Time Warner
Storm Water Construction Activity
Notice of Violation
0GC01081*AG**

Ms. Jennifer Allen
M/E Properties LLC
P.O. Box 8025
Zanesville, Ohio 43701

Dear Ms. Allen:

On May 21, 2008 I visited your site on 3940 North Pointe Drive. The purpose of the inspection was to determine the compliance of this site with the National Pollutant Discharge Elimination System (NPDES) permit for discharges of stormwater associated with construction activity. The inspection was conducted under the provisions of Ohio's water pollution control statutes, Ohio Revised Code (ORC) Chapter 6111. The following areas need to be addressed:

Permit Coverage

1. Part III.G.2.d.ii of the permit requires concentrated runoff and runoff from drainage areas, which exceed the design capacity of silt fence or inlet protection, to be conveyed to a sediment settling pond. Sites over 10 acres must install a sediment pond. Sediment ponds must be capable of holding 67 cubic yards of storage per on site and off site drainage acre. Sediment must be removed from the sediment pond when the design capacity has been reduced by 40 percent (this is typically reached when the pond is half full). **Ensure that all sediment ponds have adequate storage available to meet the above requirements.**
2. Part III.G.2.b.i. (Table 2) of the permit requires that any area that will lie dormant for more than 21 days, but less than a year be stabilized within 7 days of the most recent disturbance.
3. Part III.G.2.b.ii. of the permit states that operators shall stabilize channels and outfalls to prevent erosive flows. Techniques may include seeding, mulching, erosion control matting, sodding, rip rap, or rock check dams. **A channel needs to be added along the back portion of the property to divert the stormwater into the sediment pond. Silt Fence in this area cannot handle the channelized flow.**

Sediment and erosion controls for your site must meet the guidelines and design criteria set forth in the above mentioned Rainwater and Land Development manual. A copy of this manual may be obtained by contacting the Ohio Department of Natural Resources, Division of Soil and Water Conservation, at (614) 265-6610.

Within fourteen (14) days of receipt of this letter, please submit to me at this office a written notification as to actions taken or proposed to eliminate violations of the permit. Your response should include the dates, either actual or proposed, for the completion of the actions. If you have any questions, please contact me at (740) 380-5418.

Sincerely,



Philip Webb
Storm Water
Division of Surface Water

PW/dh